



P. Fix OEM display with 2 screws





10. Remove clamps from Ford OEM panel. Place clamps on new facia plate



11. facia plate with mounted OEM display



 Connect all required circuit points of Double-DIN Navigation, mount it to Double DIN facia plate, place it on the dashboard.
Connect cables of OEM display fix facia plate with mounted OEM display above Double-DIN Navigation

© 12/2008 ALL RIGHTS RESERVED. Technical changes possible. No liability for misprints.



Installation Manual Double DIN Kit

Ford Fiesta 2009-> Models with display only Info: Hazard light switch by Ford (No.: 15 19 127) may be required

Colour	Part-No.: Double DIN	Part-No.: with pocket
black	381114-21-1	281114-21-1
silver	381114-21-2	281114-21-2

Compatible with double DIN devices







1. Unclip the display panel

2. Remove the display panel

- 3. Remove the 4 screws of the OEM head unit
- the OEM head
- screws of unit

4. Remove the OEM head unit

Dismount the air vents

Mount the air vents to the new facia plate



5. Remove the middle bar (cut at the position marked with arrows)

 Remove OEM display. Cut away overlapping pins
left and right

7. Mount OEM display to facia plate:

Turn facia plate upside down

Place OEM display top like shown on the picture

 Push OEM display bottom until it snaps in



