


# PN2 STORM



#### TECHNICAL DRAWING



#### **D**ESCRIPTION

Powerful electropneumatic bitonal horn, harmoniously tuned. Compact dimensions. Easy to install, without connecting pipes! This horn allows you to be heard at the moment of impending danger on the road. High reliability engine! Ideal for bikes (suitable for surface mounting), cars, SUV, RV, etc. ..

#### TECHNICAL SPECIFICATIONS

		PN2 Storm	
Nominal Voltage	V	12 (24)	
Current consumption (at 24V)	A	± 18A (9A)	
Sound Level at 2 m	dB(A)	110	
Fundamental Frequency	Hz	670 (high) and 530 (low) Hz ±5%	
Sound		Harmonized twin tone	
Reliability		50.000 on/off cycles	
Operating temperature	°C	-20 +80	
Approved to ECE and ECC directives		Yes	
Electromagnetic compatibility		Yes	
Main Use		bikes, cars, SUVs, RVs	

## PHOTO DETAILS









#### PACKAGE SIZES

		PN Storm
Package size	mm	160 x 91 x 125 (h)
Product weight including package	kg	0,740
Outer package size	mm	315 x 290x 390 (h)
Quantity per outer package	nr	18
Outer package weight including products	kg	14,7

### PACKAGING



Descriptions, values and illustrations contained in this catalogue are to be considered purely as an example. LEB reserves the right to make the most appropriate changes to the models in order to improve quality, construction and commercial characteristics of such products.